PAPER • OPEN ACCESS

Road construction project waste material recommendations

To cite this article: Mega Waty and Hendrik Sulistio 2019 IOP Conf. Ser.: Mater. Sci. Eng. 650 012031

View the article online for updates and enhancements.

You may also like

- Report of IRPA task group on issues and actions taken in response to the change in eye lens dose limit Marie Claire Cantone, Merce Ginjaume, Colin J Martin et al.
- Visualization of energy-environmenteconomy system research characteristics and hotspots evolution trends based on <u>CiteSpace</u>
 Xiaoxuan Kao, Wensheng Wang, Qingyun Kao et al.
- <u>Surfing the internet with a BCI mouse</u> Tianyou Yu, Yuanqing Li, Jinyi Long et al.



The Electrochemical Society Advancing solid state & electrochemical science & technology

242nd ECS Meeting

Oct 9 – 13, 2022 • Atlanta, GA, US Early hotel & registration pricing ends September 12

Presenting more than 2,400 technical abstracts in 50 symposia

The meeting for industry & researchers in

ENERGY TECHNOLOG







This content was downloaded from IP address 103.74.170.5 on 26/08/2022 at 03:38

Road construction project waste material recommendations

Mega Waty 1* and Hendrik Sulistio¹

¹Universitas Tarumanagara, Jl. Let. Jend. S. Parman No.10, Jakarta 11470, Indonesia

* mega@ft.untar.ac.id

Abstract. After risk identification and risk analysis done, so risk response is carried out. Risk response is handled by the service provider. Recommendation is the final result of risk management of road construction project waste material. The recommendation is the aggregate B and Ready Mix Concrete is necessary to pay attention to the waiting time and pay attention to the critical trajectory on material scheduling so that breakdowns and scheduling updates are made per week. Need to pay attention to rainfall and implementation methodology. Recommendations for lean concrete waste material are necessary to pay attention to the waiting time and pay attention to the critical trajectory on material scheduling so that breakdowns and scheduling updates are carried out per week. Need to pay attention to rainfall and implementation methodology. And the causes for minimizing waste material must be considered.

1. Introduction

Risk Analysis was carried out on 51 road construction projects which stated that Aggregate B, Concrete Ready Mix and Lean Concrete which produced a number of causes of waste material and most have a high risk rating is emphasis on time and cost emphasis (Waty and Sulistio, 2019)


And now will do recommendation for waste material on road construction project after risk response.

2. Respon risk

The Risk Response generates risks received by the contractor on the first worksheet and on the second worksheet results in transfers to the implementing contractor because the contractor as the service provider must accept the consequences if a problem occurs except natural disasters and the handling of the most important risks and who handles them. After the risk response is generated, recommendations are sought. Before recommendations are made, Focus Group Discussions are conducted.

3. Focus group discussion

Group Discussion is conducted to get the expected recommendations. There were seven FGD participants. Focus Group Discussion (FGD) is a way of several ways that are used to gather opinions or perceptions from experts in their fields, thus it can be used for input into a study. The discussion invites experts at a specific place and time. It starts with giving a presentation beforehand on the model that has been obtained then the analysis that produces the sources and causes of the waste material that has been produced, then a discussion is held to determine the right recommendations.



Expert Judgment

Expert Judgment are urgently needed at the meeting. There are about 35 questions that need to be made recommendations. For example, one of the questions is taken number one, which is information on road design drawings that are less complete.

Expert Judgment 1:

Recommendations for the causes of incomplete road design drawing information are necessary to verify before the auction is conducted.

Expert Judgment 2:

Recommendations are: It is necessary to do a typical picture with only long and cross section drawing. The recommendation is to disagree with the expert 1

Expert Judgment 3

Recommended factors for incomplete road design image information.

The recommendation is to agree with expert 1 but also agree with expert 2 because if expert 1 only discusses the auction and not too detailed. But agree with expert 2 because it is more detailed.

Expert Judgment 5

The recommendation is to agree with expert 1 and expert 2 by adding design details to avoid change orders.

Expert Judgment 6

Recommendation for the causes of incomplete road design image information is to agree with expert 5. Expert Judgment 7

Recommendations The factors that cause image information to be incomplete are to agree with expert 1 and expert 2

Expert Judgment 4

Recommendations The factors that cause image information to be described as incomplete are those that do not agree with expert 5.

4. Result dan discussion

From the Focus Group Discussion produces recommendations, where there is one recommendation, namely Road Construction Project recommendations recommendations as listed in Table 1 below.

Recommendations for the Road Construction Project relating to material management which will be discussed below.

Table 1. Minimization of material waste for road construction project. (a)

Waste Material Aggregate B				
Source: Design				
Causes:				
- Information on road of	lesign drawings that are incomplete			
Minimization recomme	endations:			
- Verification needs to	be done before the auction is carried out, not only with typical long and cross			
section, but with detail	ed design so as to avoid change order.			
Source: Material Procu	rement			
Order errors result in e	xcess or lack of material for			
Minimization recomme	endations:			
- Orders must be made	in accordance with auction requirements, needs and looking for responsible			
suppliers.				
Source: Material Hand	ling Causes:			
- Errors in the use of m	aterials that need to be replaced, for example, do not comply with specified			
specifications such as a	brasion and gradation and aggregate grain hardness			
- Material sent in less c	ondition.			
- The amount of materi	al needed is not clearly known because of imperfect planning.			

Table 1. Minimization of material waste for road construction project. (b)

- Measurement of inaccurate field dimensions resulting in excess volume.

Minimization recommendations:

- Must be in accordance with the reference standards including SNI 03-4141-1996, SNI 1744: 2012 and SNI 7619: 2012 so that the aggregate used has a minimum immersion CBR value of at least 60% and a plasticity index of 0-10.

- Find the appropriate borrow pit and avoid irresponsible suppliers.

- Review design with re-measurement so that when shop 0%, a shop drawing can be made.

Leveling of sub grade must be properly checked with Theodolite at each implementation and confirmed solid soil conditions.

Source: Behavior Control

Factors that cause:

- Material scheduling control deviations

- Deviations in controlling material costs

Minimization recommendations:

- Need to pay attention to the waiting time and pay attention to the critical trajectory on material scheduling so that breakdowns and scheduling updates are carried out per week. Need to pay attention to rainfall and implementation methodology. It is necessary to pay attention to the Variant Schedule (SV) and Cost Variant (CV) because if SV and CV = negative then the work is finished late and costs higher than the budget.

- Paying attention to the Work Breakdown Structure of each type of work so that if there is a delay in immediate handling, for example if there is a 5% delay, a meeting must be held and if the delay of 10% is necessary, the Show Cause Meeting should also take into account the weather and

implementation methodology. It is necessary to pay attention to the Variant Schedule (SV) and Cost Variant (CV) because if SV and CV are negative so the work is finished late and costs higher than the budget.

Waste	Material	Lean	Concrete	
-------	----------	------	----------	--

Source: Design

Causes:

- Order error due to choosing different product specifications

Minimization Recommendation:

- Must pay attention to specifications that are in accordance with the required terms of reference.

Source: Material Handling

Causative factors

- Material sent in less condition

Minimization recommendations:

Pay more attention to the sub contractor to get the right volume according to the specifications.

Source: Behavior Control

Causes:

- Material scheduling control deviations

Minimization Recommendation:

Need to pay attention to the waiting time and pay attention to the critical trajectory of project scheduling so that breakdowns and scheduling updates are made per week. Need to pay attention to rainfall and implementation methodology. It is necessary to pay attention to the Variant Schedule (SV) and Cost Variant (CV) because if SV and CV are negative so the work is finished late and costs higher than the budget.

Table 1. Minimization of material waste for road construction project. (c)

Waste Material Concrete Ready Mix

Source: Behavior Control

Causes:

- Deviations in controlling material costs

Minimization Recommendation:

- Paying attention to the Work Breakdown Structure of each type of work so that if there is a delay in immediate handling, for example if there is a 5% delay, a meeting must be held and if the delay of 10% is necessary, the Show Cause Meeting should also take into account the weather and implementation methodology. It is necessary to pay attention to the Variant Schedule (SV) and Cost Variant (CV) because if SV and CV are negative so the work is finished late and costs higher than the budget.

Source: Material Handling

Causes:

- Damage to material in the place due to the slow cutting of concrete

Minimization recommendations:

- Immediately conduct a special team to cut before 8 hours.

Source: Implementation

Causes:

- Work accidents in the field.

- Unreliable equipment

Minimization recommendations:

- Applying the correct K3 in accordance with OHSAS or SMK3 with clear and precise PPE.

- Repairing tools or using appropriate equipment in accordance with the requirements in the work

reference frame of at least 90% of its novelty.

5. Recommendation

The recommendations for the causes of each of the most extreme materials are as shown below.for Road Construction Projects:

1. B Aggegate

Source: Behavior Control

Cause: Material scheduling control deviations

Recommendation: Need to pay attention to the waiting time and pay attention to the critical trajectory on material scheduling so that breakdowns and scheduling updates are carried out per week. Need to pay attention to rainfall and implementation methodology. It is necessary to pay attention to the Variant Schedule (SV) and Cost Variant (CV) because if SV and CV are negative so the work is finished late and costs higher than the budget.

2. Lean Concrete Source: Behavior Control

Cause: Material scheduling control deviations

Recommendation: Need to pay attention to the waiting time and pay attention to the critical trajectory on material scheduling so that breakdowns and scheduling updates are carried out per week. Need to pay attention to rainfall and implementation methodology. It is necessary to pay attention to the Variant Schedule (SV) and Cost Variant (CV) because if SV and CV are negative, so the work is finished late and costs higher than the budget.

3. Concrete Ready Mix Source: Behavior Control

Cause: Deviation in controlling material costs

Recommendation: Pay attention to the Work Breakdown Structure of each type of work so that if there

IOP Publishing

IOP Conf. Series: Materials Science and Engineering 650 (2019) 012031 doi:10.1088/1757-899X/650/1/012031

is a delay in immediate handling, for example, if a 5% delay occurs, a meeting must be held and if the delay of 10% is necessary, the Show Cause Meeting should also take into account the weather and implementation methodology. More concentration on the cost of implementation. It is necessary

to pay attention to the Variant Schedule (SV) and Cost Variant (CV) because if SV and CV are negative so the work is finished late and costs higher than the budget.

6. Conclusion

The causal factors that need to be considered to minimize waste material with risk management during the implementation phase of the road contruction project are as follows:

- a. Waste Material B Aggregate Causes:
- Information on road design drawings that are incomplete.
- Order errors result in material overload or lack.
- Errors in the use of materials that need to be replaced, for example, do not conform to specifications specified such as abrasion and gradation and aggregate grain hardness.
- Material sent in less condition.
- The amount of material needed is not clearly known because of imperfect planning.
- Measurement of inaccurate field dimensions resulting in excess volume.
- Material scheduling control deviations.
- Deviations in controlling material costs.

b. Waste Material Lean Concrete Causes:

- Error ordering because choose a different specification.
- Material sent in less condition.
- Material scheduling control deviations.


c. Waste Material Concrete Ready Mix Causes:

- Deviations in controlling material costs.
- Damage to material in the place due to the delay in cutting concrete.
- Work accidents in the field.
- Unreliable equipment.

References

- [1] Al-Bahar J and Crandall K 1990 Systematic risk Management approach for construction projects *Journal of Construction Engineering and Management* **116**(3) pp 533-546
- [2] Bossink B A G and Browers H J H 1996 Construction waste: Quantification and source evaluation *Journal of Construction Engineering and Management* **122**(1) pp 55–60
- [3] Choi H H and Mahadevan S 2008 Construction Project Risk Assessment Using Existing Data base and Project Specific Information Journal Of Construction Engineering And Management 134(11) pp 894-903
- [4] Ekanayake L and Ofori G 2000 Construction material waste source evaluation *Proc. Strategies for sustainable built environment* Pretoria pp 23-25
- [5] Farmoso C T, Soibelman L M, Cesare C D and Isatto E L 2002 Material waste in building industry: Main causes and prevention *Journal of Construction Engineering and Management* 128 (4) pp 316–325
- [6] Foley P, Howard G and Ian M 1984 Future of the Sheffield Economy: an investigation using the Delphi Method Departement of Town and Regional Planning, Faculty of Architectural Studies, University of Sheffield

- [7] Gavilan R M and Bernold L E 1994 Source evaluation of solid waste in building construction Journal of Construction Engineering and Management **120**(3) pp 536 – 552
- [8] Hanna A S, Thomas G and Swanson J R 2013 Constructions risk identification and allocation cooperative approach *Journal Of Construction Engineering And Management* **139**(9)
- [9] Jaselskis E J and Russels J S 1992 Risk Analysis Approach To Selection of Contractor Evaluation Method Journal Of Construction Engineering And Management 118(4) pp 814-821
- [10] Loosemore M and Teo M 2001 A Theory of waste behaviour in the construction industry Journal Construction management and economic pp 741-751
- [11] Polat G and Ballard G 2004 Waste in Turkish Construction Need for lean construction techniques Proceedings of the 12th Annual Conference of the International Group for Lean Construction IGLC-12" August Denmark pp 488-501
- [12] Waty M and Sulistio H 2019 Identifikasi Risiko Lanjutan Terhadap Sumber dan Penyebab Material Waste Proyek Konstruksi Jalan Journal Media Komunikasi Teknik Sipil, ID 21817 Semarang,Indonesia (Waiting Assignent)
- [13] Waty M and Sulistio H Early Risk Identification On Source and Causes of Waste Road Project Construction Materials Tarumanagara International Conference On the Application of Technology and Engineering Jakarta Indonesia Nov 22-23 2018 IOP Conf. Series: Materials Science and Engineering 508 (2019) 012008, doi:10.1088/1757-899X/508/1/012008
- [14] Waty M, Alisyahbana S, Gondokusumo O, Sulistio H, Hasyim C, Setiawan M I and Ahmar A S 2018 Modeling of Waste Material Cost on Road Construction Projects *International Journal Of Engineering & Technology* 7(2) pp 474-477
- [15] Waty M and Sulistio H 2019 Risk Analysis Waste Material on Road Construction Project " International Review of Civil Engineering-Praise Worthy Prize, ID 17207(In Review)



⊟ 5·0 ÷	③LINTA ⊙ SISTER 10P pdf ③ 1 ③ 1 ⑤	1 🛛 🚱 sertifik 🛛 🚱 7023-1 🗣 Merge 🛛 🍖 DAMPi 🖉 jurnala	▼ - □ X			
File Home Insert Design Layout References I						
Calibri (Body) • 11 • A* A* A* A*	← → C i scimagojr.com/journalsearch.php?q=197002008318tip=sid&clean=0 i ☆ ▲ ▲ ○ ◆ ▲ □ ◎ :					
Paste \checkmark Format Painter B $I \sqcup \neg abc x_2 x^2$ $\land \neg a^2 \neg \Delta \neg$						
Clipboard rs Font rs						
	H-INDEX	PUBLICATION TYPE	ISSN			
N						
	48	Conferences and Proceedings	17578981, 1757899X			
-	1 0					
-						
er - -						
n 						
	COVERAGE	INFORMATION				
- 17 -						
	2009-2021	Homepage				
-		How to publish in this journal				
		mse@iop.org				
o. 						
- 			① ×			
4	Get a Free Trial Today - Accounting,					
	analytics & more		OPEN			
-	-	peer-reviewed content. taylorandfrancis.com				
-						
Page 1 of 1 0 words D2 Indonesian	🔁 Waty_2019_IOP_Cpdf \land 🔁 sertifikat_EC00202pdf	↑ Sertifikat_EC00202pdf ↑ Duku PENYEBAB	Cpdf ^ Show all X			
Page 1 of 1 0 words LB indonesian	n n n n n n n n n n n n n n n n n n n	R 🗢 🚥 🗖 🧿 🖉				

⊟ 5 · Ø ∓	🕲LINTA 🔮 SISTER 🕪 pdf 🔇 1	3 1 3 1 3 sertifik 3 7	1023-1 🍫 Merge 资 DAMP: 🔇 jurnala 🜆 IOF 🗴	<pre></pre>
File Home Inset Design Layout References Image & Guitori Galibri (Body) - 11 - A^* A^* Aa - A A	← → C 🔒 scimagojr.com/journa	lsearch.php?q=19700200831&ttip=sid&clean=0 Hir	ndawi	è☆ 🖿 🖾 🕈 🖬 🚳 ፤ Open >
Clipboard r. Font r	 SJR 0.28 0.24 0.2 0.24 0.2 0.2 0.2 0.16 2010 2010	× ⊞ 012 2014 2016 2018 2020 ■ self-Cites × ⊞	Total Documents 40k 20k 0 2009 2011 2013 2015 2017 Citations per document 0.6	
Page 1 of 1 0 words B Indonesian	analytics Expand your resear	ee Trial Today - Accou & more ch today with trusted peer-reviewed content	OPE 1. taylorandfrancis.com 100202pdf ^ 12 buku PENYEBAB Cpdf -	

	🔕LINTA 😒 SISTER	10P pdf 🕲 1 🕲 1 🕲 se	rtifik 🕙 702	13-1 🎔 Merge 🍥 DAMP: 🔇 jur	mala 500 IOF × +	×
File Home Insert Design Layout References	← → C 🔒 sc	magojr.com/journalsearch.php?q=19700200831&ttip=side	&clean=0		ið 🖈 📒 🔤	🕈 🗯 🖬 🚺 🗄
Calibri (Body) • 11 • A A Ad • *		% International Collaboration	≈ ==	Citable documents Intervention Non-citable	itable documents 🛛 🖄 🖽	
Clipboard rs Font		40		80k	_	
Clipboard rs Font r		20 2009 2011 2013 2015 2017 2019	2021	40k 0 	15 2017 2019 2021	I
		Cited documents Uncited documents	☆			
N		80k	<u> </u>	IOP Conference Series: Materials Science and	 Show this widget in your own website 	
		40k		Not yet assigned quartile	Just copy the code below and paste within your html	
		SJR 2021	code: 			