

SURAT TUGAS

Nomor: 1156-R/UNTAR/PENELITIAN/III/2022

Rektor Universitas Tarumanagara, dengan ini menugaskan kepada saudara:

HENNY WIYANTO, Ir., M.T.

Untuk melaksanakan kegiatan penelitian/publikasi ilmiah dengan data sebagai berikut:

Judul : Critical Index Determination Method on Visual Assessment of Concrete Damage for Buildings
Nama Media : IOP Conference Series: Materials Science and Engineering
Penerbit : IOP
Volume/Tahun : 2019
URL Repository :

Demikian Surat Tugas ini dibuat, untuk dilaksanakan dengan sebaik-baiknya dan melaporkan hasil penugasan tersebut kepada Rektor Universitas Tarumanagara

02 Maret 2022

Rektor



Prof. Dr. Ir. AGUSTINUS PURNA IRAWAN

Print Security : 9693af826cf98e84a78fd7db5f99f3df

Disclaimer: Surat ini dicetak dari Sistem Layanan Informasi Terpadu Universitas Tarumanagara dan dinyatakan sah secara hukum.

PAPER • OPEN ACCESS

Critical Index Determination Method on Visual Assessment of Concrete Damage for Buildings

To cite this article: Henry Wiyanto *et al* 2019 *IOP Conf. Ser.: Mater. Sci. Eng.* **508** 012003

View the [article online](#) for updates and enhancements.



IOP | ebooks™

Bringing you innovative digital publishing with leading voices to create your essential collection of books in STEM research.

Start exploring the [collection](#) - download the first chapter of every title for free.

Critical Index Determination Method on Visual Assessment of Concrete Damage for Buildings

Henny Wiyanto*, David Lie and James Kurniawan

Department of Civil Engineering, Faculty of Engineering, Universitas Tarumanagara, Jakarta, Indonesia 11440

*hennyw@ft.untar.ac.id

Abstract. Visual Assessment is an initial assessment of the concrete condition of a building (non-destructive test). There are multiple types of concrete damage, so it is necessary to identify the type of damage that could be assessed visually. To find out the critical level of each type of concrete damage, a Critical Index method is needed. Based on the analysis sets, the range of Critical Index is 0 to 4. The value of 0 indicates a very good Critical Index of concrete, whereas the value of 4 shows a very bad Critical Index of concrete. The value of 0 can be interpreted as the concrete is not damaged and 4 means that the concrete is not acceptable. Determination of Critical Index method can be used to determine the Critical Index of any type of damage to the concrete in a building and to determine the level of damage according to each type of damage.

Keywords: Critical Indeks, Concrete Damage, Visual Assessment.

1. Introduction

Concrete is one of the main components forming a building structure consisting of shearwall, columns, beams, and slab. As time and natural condition go by, a building can suffer damage on parts of the building structure. To be able to find out the concrete conditions in reinforced concrete construction, buildings are evaluated using the Visual Assessment method. Visual Assessment is a non-destructive assessment method of the concrete condition of a building, so this method can be first step to assess the condition of damage to concrete structures. Based on these needs, it is necessary to identify the type of damage to the concrete structure visually and set Critical Index for each type of damage. The method of determining the Critical Index on the damage to concrete structure of this building is expected to be a reference for conducting this assessment.

2. Method

Determination of the Critical Index is carried out with the following steps:

2.1. Identification of damage type

Identification of types of concrete damage visually taken from various literature. The literature consists of national and international regulations and the results of previous similar studies published at the international level [1-5], [7].

2.2. Determination of Critical Index

Determination of the Critical Index will be carried out on all types of concrete damage that have been identified. Determination will be done with the following steps:



2.2.1. Data Collection

Data collection was carried out by assessing each type of concrete damage through a questionnaire. Assessments are obtained based on expert opinion consisting structure consultants, lecturer, research scientist, and an experienced contractor in the field of reinforced concrete construction. The range of Critical Index is 0 to 4. The value of 0 indicates a very good Critical Index of concrete, whereas the value of 4 shows a very bad Critical Index of concrete. The value of 0 can be interpreted that the concrete is not damaged and 4 means that the concrete is not acceptable. Identification of Critical Index of Concrete Damage can be seen as in Table 1.

Table 1. Identification of Critical Index of Concrete Damage

Critical Index	Criteria	Identification of Damage
0	Very Good	No action is needed
1	Good	Acceptable, No need to repair
2	Moderate	Not acceptable, Repair needed
3	Poor	Not acceptable, Needs immediate repair
4	Very Poor	Cannot be maintained

2.2.2. Data Processing

Data processing intends to determine the Critical Index for each type of concrete damage that determined using the Relative Important Index method. To find out the comparison of one type of damage with other types of damage will be used the Analytical Hierarchy Processing method [6].

3. Results and Discussion

This study was applied to buildings with reinforced concrete construction. Visual Assessment is an assessment using the eye senses to determine the type of damage that occurs in a concrete structure. Damage that occurs in the concrete structure is identified and the Critical Index for each type of concrete damage determined by following formula:

$$CI_{Tn} = \sum_{t=0}^4 \left(\frac{t \cdot C_t}{N} \right)$$

Explanation:

CI_{Tn} : Critical Index Damage

C_t : Number of responses at Critical Index Level

t : Critical Index Level

N : Total of response

Damage is grouped according to structural elements, namely shearwall, column, beam, and slab. Each structural element has a different critical weight namely cw_{sh} , cw_c , cw_b , and cw_s . It is probable that in some parts of the structure occur more than one type of damage. If there is more than one type of damage in the same location, it is necessary to know the level of damage between the type of damage one with the other types of damage. So the level of damage in that location can be determined. This can be seen as in Table 2 dan Table 3.

Table 2. Comparison Matrix of Concrete Damage

Damage Type (T)	T₁	T₂	T_n
T₁	CI _{T11}	CI _{T12}	CI _{T1n}
T₂	CI _{T21}	CI _{T22}	CI _{T2n}
T_n	CI _{Tn1}	CI _{Tn2}	CI _{Tnn}
Total	CIT_{T1}	CIT_{T2}	CIT_{Tn}

Table 2 portrays the comparison between one type of damage and the others, so it can be determined that Critical Index Total Damage is determined by the following formula:

$$CI_{Tnn} = \frac{CI_{Tn}}{CI_{Tn}}$$

$$CIT_{Tn} = \sum_{T=1}^n CI_{Tnn}$$

Explanation:

CI_{Tnn} : Critical Index Damage n against other Damage

CIT_{Tn} : Critical Index Total Damage

Table 3. Normalization of Comparison Matrix of Concrete Damage

Type (T)	T₁	T₂	T_n	Average
T₁	A _{T11}	A _{T12}	A _{T1n}	A_{T1}
T₂	A _{T21}	A _{T22}	A _{T2n}	A_{T2}
T_n	A _{Tn1}	A _{Tn2}	A _{Tnn}	A_{Tn}

Based on the table above, the level of damage between types of damage with one other damage is determined by the following formula:

$$A_{Tnn} = \frac{CI_{Tnn}}{CIT_{Tn}}$$

$$A_{Tn} = \frac{\sum_{T=1}^n A_{Tnn}}{n}$$

Explanation:

A_{Tnn} : Weight Critical Index Damage

A_{Tn} : Average Weight Critical Index Damage

4. Conclusion

Based on the analysis, it could be concluded that the method of determining the Critical Index could be used to determine the Critical Index of all types of damage of the concrete in a building and to know the level of damage for each type of damage. So when more than one type of damage happens in one location, the level of damage can be determined.

5. References

- [1] American Concrete Institute (ACI) Committee 201. (2008). "Guide for conducting a visual inspection of concrete in service". ACI 201.1R-08, Farmington Hills, MI.
- [2] American Society of Civil Engineers (ASCE). (2000). "Guideline for Structural Condition Assessment of Existing Buildings". SEI/ASCE 11-99, Reston, Virginia 20191-4400.
- [3] Jain, K.K. and Bhattacharjee, B. (2012). "Application of Fuzzy Concepts to the Visual Assessment of Deteriorating Reinforced Concrete Structures". *Journal of Construction Engineering and Management ASCE*. March. 138:399-408.
- [4] Mitra, G., Jain, K.K., and Bhattacharjee, B. (2010). "Condition Assessment of Corrosion-Distressed Reinforced Concrete Buildings Using Fuzzy Logic". *Journal of Performance of Constructed Facilities ASCE*. November/December.
- [5] Pragalath, H., Seshathiri, S., Rathod, H., Esakki, B., Gupta, R. (2018). "Deterioration Assessment of Infrastructure Using Fuzzy Logic and Image Processing Algorithm". *Journal of Performance of Constructed Facilities*, Vol. 32, Issue 2.
- [6] Saaty, T.L. (1980). "The Analytic Hierarchy Process". McGraw-Hill, New York.
- [7] Tirpude, N.P., Jain, K.K., and Bhattacharjee, B. (2014). "Decision Model for Repair Prioritization of Reinforced-Concrete Structures". *Journal of Performance of Constructed Facilities*, Vol. 28, Issue 2.